SONY

XM-2002GTR

Amplifier

Key Features

- 1200W max power
- 200W x 2 RMS into 4 ohms, 20Hz-20kHz @ 0.1% THD
- 500W x 1 RMS into 4 ohms, 20Hz - 20kHz @ 0.15% THD
- High Level Sensing Power On
- 1200W max power
- 200W x 2 RMS into 4 ohms, 20Hz-20kHz @ 0.1% THD
- 500W x 1 RMS into 4 ohms, 20Hz - 20kHz @ 0.15% THD
- High Level Sensing Power On
- Variable 50 - 300 Hz low pass filter
- 40 Hz EQ boost
- MOSFET output stage & power supply
- RCA & speaker level inputs
- Line level thru-put
- CEA-2006 Power Compliant

Specifications

Audio

Frequency Response: 5 - 50k Hz

Input Level: 1.2 - 12 V (Speaker level input)

Power

Power Consumption (in Operation): 1200 Watts

Output Power: Bridged into 4 ohms, THD% 500, .15

Current Drain: 48A

Output Voltage: 10.5 - 16 V

Dimensions

Weight: 11 lbs. 6 oz

Measurements: 10 7/8 x 2 1/4 x 15 7/8" (276 x 57 x 403mm)

UPC Code: 027242686717

SONY

XM-2002GTR

Amplifier

Please visit the Dealer Network for more information at www.sony.com/dn

©2006 Sony Electronics Inc.
Reproduction in whole or in part without written permission is prohibited.
Sony is a trademark of Sony. All other trademarks are property of their respective owners.
Features and specifications are subject to change without notice. Non-metric weights and measures are approximate.